

Schuller Eh'klar GmbH  
 AUSTRIA  
 Im Astenfeld 6  
 A – 4490 St. Florian  
 Tel.(0043) 07224/68 200  
 Fax(0043) 07224/68 282  
 E-Mail: office@schuller.eu  
 www.schuller.eu



St. Florian, 02.04.2013

# UV-FOLI TAPE

(Articlenumbers: 46402, 46403, 46405, 46405, 46413)

## Description:

Self-adhesive protective film for glass surfaces.

- The film is not harmful and can be completely recycled
- The film is not suitable for the protection of metals and mirrored glass surfaces
- Applications include glass, aluminium, PVC and stainless steel, wood, ceramic

## Technical data:

|                         |                              |
|-------------------------|------------------------------|
| material                | LDPE-Folie                   |
| adhesive                | Acrylat                      |
| strentgh                | 50my (±10%)                  |
| density                 | 0,922                        |
| weight                  | 46g/m2 (±10%)                |
| adhesion strength       | >80 cN/cm (AFERA 4001; Glas) |
| elongation (lengthwise) | >200%                        |
| elongation (crosswise)  | >400%                        |
| application temperatur  | -5°C - +35°C (dry surface)   |

## Application:

- Don't remove the film with sudden movements from the glass surfaces
- The film must be applied to dry and clean surface. The application must be made without fat, air bubbles or excessive stretching of the film
- The film must be removed within 4 weeks
- Test adhesion necessary

## Storage:

Storage at room temperature (between 10 ° C and +30 ° C at a relative humidity of 50%). Keep away from direct sunlight and other heat sources. In compliance with the storage conditions, the film can be stored for 6 to 12 months.